

Xantrex Accessories



T240 Autotransformer

Autotransformer or Balancing Transformer

Includes built-in dual pole 25 amp circuit breaker disconnect. Rated for 3900 watts continuous output. UL listed.

T240	120-240 volt step-up or step-down transformer, maximum continuous power 3.9kVA	\$350.00
------	--	----------



Battery Temperature Sensor

Battery Temperature Sensors

BTS/15	Battery temperature sensor with 15' cable for DR, SW, PS and UX series	\$29.00
BTS/35	Battery temperature sensor with 35' cable for DR, SW, PS and UX series	\$32.00



RC8 Remote Control

Remote Controls

RC8/50	Remote on/off control with status LED indicator for all DR, PS, TS and UX series with 50' cable	\$69.00
RC8/100	Remote on/off control with status LED indicator for all DR, PS, TS and UX series with 100' cable	\$94.00



PVGFP1 Ground Fault Protection

Ground Fault Protection

Ground fault protection is required for residential PV rooftop installations on homes in the US. UL listed. Does not include an enclosure. 100 amp DC max per pole.

PVGFP1	Ground fault protection, one pole for one solar array	\$275.00
PVGFP2	Ground fault protection, two pole for two solar sub-arrays	\$325.00
PVGFP3	Ground fault protection, three pole for three solar sub-arrays	\$375.00
PVGFP4	Ground fault protection, four pole for four solar sub-arrays	\$425.00