

Inverters




PROsine 1000 Inverter

Xantrex

PROsine Inverters

Offering quality true sine wave output, the PROsine inverter is ideally suited for electrical systems that already have a quality multistage battery charger. Designed for recreational and industrial applications, its output is capable of handling both heavy duty and smaller, multiple AC loads. A removable LCD display can be mounted remotely for control and monitoring. The powersave mode draws only 1.5 watts under no load. 230VAC/50 Hz models available. Two-year warranty.

Model	Efficiency	DC Voltage Input	Continuous Power	AC Volts Output	Dimensions	Weight	MSRP
PROsine 1000	89%	12 V	1.0kVA	120VAC	15.4" x 11.5" x 4.5"	14.5 lbs	\$890.00
PROsine 1000/24V	90%	24 V	1.0kVA	120VAC	15.4" x 11.5" x 4.5"	14.5 lbs	\$980.00
PROsine 1800	89%	12 V	1.8kVA	120VAC	15.4" x 11.5" x 4.5"	16.5 lbs	\$1,300.00
PROsine 1800/24V	90%	24 V	1.8kVA	120VAC	15.4" x 11.5" x 4.5"	16.5 lbs	\$1,430.00
<u>Models with hardwire/15 amp AC Transfer Relay:</u>							
PROsine 1000 HW/TR	89%	12V	1.0kVA	120VAC	15.4" x 11.5" x 4.5"	14.5lbs	\$940.00
PROsine 1000/24V HW/TR	90%	24V	1.0kVA	120VAC	15.4" x 11.5" x 4.5"	14.5lbs	\$1,030.00
PROsine 1800 HW/TR	89%	12V	1.8kVA	120VAC	15.4" x 11.5" x 4.5"	16.5lbs	\$1,350.00
PROsine 1800/24V HW/TR	90%	24V	1.8kVA	120VAC	15.4" x 11.5" x 4.5"	16.5lbs	\$1,480.00
Remote Interface Kit – Allows LCD panel to be removed - includes 25' of cable and replacement on/off switch panel for inverter cavity							\$50.00



PROsine 2.5 Inverter

PROsine Inverter/Chargers

A powerful all-in-one solution, PROsine inverter/chargers deliver clean true sine wave output power for all types of appliances along with three-stage charging for longer battery life. Inverters include a full function remote control panel and battery temperature sensor. Built in transfer switch. CSA/NRTL certified. Two-year warranty.

Model	Efficiency	DC Voltage Input	Continuous Power	Charger Current	AC Volts Output	Dimensions	Weight	MSRP
PROsine 2.0	87%	12 V	2.0kVA	100 A	120VAC	17.7" x 11" x 5.7"	24 lbs	\$2,000.00
PROsine 2.0 w/GFCI outlets	87%	12 V	2.0kVA	100 A	120VAC	17.7" x 11" x 5.7"	24 lbs	\$2,000.00
PROsine 2.5	88%	12 V	2.5kVA	100 A	120VAC	20.0" x 15" x 7.0"	32 lbs	\$2,600.00
PROsine 2.5/24V	88%	24 V	2.5kVA	50 A	120VAC	20.0" x 15" x 7.0"	32 lbs	\$2,860.00
PROsine 3.0	88%	12 V	3.0kVA	120 A	120VAC	20.0" x 15" x 7.0"	32 lbs	\$3,000.00
PROsine 3.0/24V	88%	24 V	3.0kVA	60 A	120VAC	20.0" x 15" x 7.0"	32 lbs	\$3,300.00
Temperature Sensor – Remote battery temperature sensor for PROsine 2.5/3.0								\$30.00