

SHURflo



SHURflo Power Twin Pump



SHURflo 902-200 Controller



SHURflo 2088 Surface Pump

SHURflo 2088 series surface pumps offer an inexpensive, simple to rebuild, rugged booster pump that can deliver up to 3.6 GPM from a 12 or 24 VDC battery bank. A good pump for a cabin or small home system. They can run dry without damage and are UL listed. The 9300 model submersible pump will provide many years of service and can be rebuilt in the field with simple tools. This pump has become a favorite with ranchers, remote homeowners and missionaries for the small solar arrays needed and ease of use. This pump produces around 1 GPM from up to 220 feet of lift. The Power Twin Pump is one of the most efficient high-flow, self-priming pumps and features a Santoprene® diaphragm, Viton® valves, and a thermally protected motor with heat sink. Includes dual manifold system with 5/8" hose barb ports. One-year warranty.

Model	Voltage	Current	Flow Rate	Weight (lbs)	MSRP
Demand Pumps					
2088-443-144 Standard	12VDC	9.1A	3.6GPM	4.8	\$118.00
2088-514-145 High Flow	12VDC	9.0A	3.6GPM	6.8	\$189.00
2088-414-534 Premium	12VDC	9.0A	3.6GPM	6.8	\$254.85
2088-474-144 Standard	24VDC	2.71A	3.0GPM	4.9	\$139.70
2088-574-534 Premium	24VDC	4.5A	3.6GPM	6.4	\$256.20
2088-594-154 Standard	115VAC	0.94A	3.3GPM	5.1	\$191.00
170-061-29 Strainer for 2088's	Twist on strainer, stainless steel screen, 1/2" MPT inlet, 1/2" FPT outlet				\$12.00
4111-035 Power Twin	12VDC	12.1A	6.25GPM	7.9	\$299.00
4000-421-114 Power Twin	24VDC	9.0A	6.5GPM	8.0	\$299.00
Submersible Pump					
9325-043-011 Submersible	24VDC	2.6A	1.0GPM	6.0	\$745.00
902-100 Pump Controller	24VDC with float switch terminals			2.0	\$132.00
902-200 Pump Controller	12/24VDC with weatherproof enclosure, float switch terminals and water level probes			8.0	\$325.00

Vertical Lift
220ft